



Shingle Starter Strip™

Self-Adhering Roofing Composite

Key Properties

- **No need to cut tabs or invert shingles saving time and labor costs**
- **Seal down strip prevents wind uplift**
- **Easy peel & stick application**

Description

York Shingle Starter Strip is a proprietary, self-adhering composite. **York Shingle Strip** is composed of a self-adhering back to seal to the roof deck or underlayment, a tough granular surface will form a barrier to physical damage while providing superior UV ray protection and a seal down strip to prevent shingle uplift.

York Shingle Starter Strip is composed of the same unique materials found in other York membranes that allow the material to seal around nail penetrations and provide waterproofing capabilities.

York Shingle Starter Strip is provided in single rolls that are 7.2" wide by 33'4" long. **Shingle Starter Strip** is self-adhering and cold applied. No special adhesives or equipment are necessary to install **York Shingle Starter Strip**.

Uses

York Shingle Starter Strip is designed to be used as an easy, cost saving alternative to the traditional method of cutting and inverting shingles to form a starter course.

May be used as a rake edge strip to prevent wind uplift.

Application

Substrate Preparation

- Surfaces must be clean, dry and smooth. Install **York Shingle Starter Strip** over any York membrane.

Application

- Roll **York Shingle Starter Strip** into place. Along the eave edge, apply **York Shingle Starter Strip** over ice and water protection membrane and drip edge. **York Shingle Starter Strip** may be applied over existing shingles. Remove the release sheet. Roll membrane firmly to insure uniform contact with substrate.

York Shingle Starter Strip is

formulated to be installed in ambient temperatures of 40°F and above. When applying **York Shingle Starter Strip** in ambient temperatures below 40°F, store at room temperature until use, spot nailing may be required.

YORK
Since 1935

TM

TECHNICAL DATA
YORK SHINGLE STARTER STRIP

PROPERTY	MINIMUM VALUE	TEST METHOD
Tensile Strength	Longitudinal (md) 48lbs/in width Transverse (cd) 35lbs/in width	ASTM D 412
Tear Resistance	Longitudinal (md) 20 lbs Transverse (cd) 20 lbs	ASTM D-4073
Elongation to Break	320%	ASTM D 412
Pliability, 180°, 1" mandrel -25°F (-4°C)	Pass	ASTM D 146
Puncture Resistance	50 lbs	ASTM E 154
Permeance	0.05 perms (max)	ASTM E 96B
Length	33.3 feet	
Width	72 inches	
Thickness	75 mils	ASTM D-5147

Safety, Storage and Handling

Pallets of **York Shingle Starter Strip** shall not be double stacked on the job site. Provide cover on top and all sides, allowing for adequate ventilation. Avoid prolonged and repeated contact with the skin.

Consult the Material Safety Data Sheet for the best available information on the safe handling, storage, personal protection, health and environmental considerations.

