



Product Submittal

Cop-R-Tite™ Flashing Mastic

Description

Cop-R-Tite flashing mastic is a compounded composition of asphalt, mineral stabilizers, and interfiber. It is manufactured to a trowel grade consistency, which will provide a durable, elastic coating highly resistant to weathering while providing excellent adhesion properties. **Cop-R-Tite** flashing mastic performs well over a wide range of temperature and weather conditions. It complies with all requirements of Federal Specifications SS-C-153, Type 1 and ASTM 4586-88, Type 1 and SSPC No. 12.

Description & Benefits:

Compatible with:

- Concrete, Brick and Masonry, Gypsum Sheathing, Wood, Slat
- Provides a strong, flexible waterproof barrier with excellent adhesion.
- Asphalt Mastic allows for expansion or contraction caused by temperature fluctuations or building movement.

Uses:

Cop-R-Tite flashing mastic is the preferred mastic to be used while splicing copper flashings. Material should be overlapped a minimum of 4" and a coating of **Cop-R-Tite** applied to yield a 30sf per gallon coverage. Mastic application should be held back at least 1" from the exterior of the wall. **Cop-R-Tite** flashing mastic should be spotted to vertical surfaces to receive flashing. **Cop-R-Tite** mastic will hold the flashing in place while the masonry sets. Flashing should be secured in a reglet or masonry joint or otherwise mechanically fastened. Mastic application should be held back at least 1" from the exterior of the wall.

Packaging:

- 30oz tubes, with 20 tubes to a carton
- 5gal pail

Date: _____

Project: _____ Project Address: _____

Architect Firm: _____ Project Architect: _____

Approved: _____ Not Approved: _____ Why not approved: _____

Contractor: _____ Contactor Address / Phone #: _____

Bid Date: _____

Notes: _____

York Manufacturing, Inc.

Telephone: (800) 551-2828

Website: www.yorkmfg.com