



# Product Submittal

## HomeSeal™

### Description

HomeSeal™ flashing is a 25 mil. thick membrane consisting of a self-adhering rubberized laminated to a high density cross laminated polyethylene film. A siliconized release liner prevents the product from sticking to itself in the roll.

### Description & Benefits:

- Waterproof Barrier at flashing areas to prevent wall assembly leaks
- Self-adhesive nature allows for easy installation on concrete, masonry, gypsum, steel and wood substrates.

### Uses:

- Through-Wall Flashing
- Curtain Wall Perimeter Flashing
- Jamb Closer Flashing
- Roof to Parapet Flashing
- Repair Tape for flashing, air barriers, etc.
- Transition Membrane (air barriers, roofing, waterproofing)
- Window and Door Tape
- Window and Door Pan

### ACCESSORIES:

- UniverSeal sealant US-100
- SS Termination Bar
- T-96 Termination Bar
- Stainless Steel Inside Corners
- Stainless Steel Outside Corners
- Stainless Steel End Dams
- Stainless Steel Drip Edge
- Weep Armor™

### Application

#### Substrate Preparation

- All surfaces must be clean, dry and smooth. Structural concrete should be cured a minimum of 7 days.

#### Primer

- **If needed** prime surface with solvent or Emulsion Base Primer. Allow primer to dry completely before installing **York HomeSeal** membrane.

#### Application

- Cut **York HomeSeal** into manageable lengths. Remove the release sheet. Apply membrane from the lowest point upward, overlapping horizontal edges in shingle fashion. Roll membrane firmly to insure uniform contact with substrate. Overlaps should be sufficient to insure consistent adhesion to the substrate. Reinforcing strips on all inside and outside corners as well as mechanical fastening to door and window frames is strongly recommended. Seal all terminations, detailing and protrusions.
- **York HomeSeal** is formulated to be installed in ambient temperatures of 40°F and above. When applying **York HomeSeal** in ambient temperatures below 40°F, store **York HomeSeal** at room temperature until use; if needed, prime the substrate with primer to insure good initial adhesion.
- **York HomeSeal** should not be left exposed for more than 30 days.

Date \_\_\_\_\_

Project: \_\_\_\_\_ Project Address \_\_\_\_\_

Architect Firm: \_\_\_\_\_ Project Architect \_\_\_\_\_

Approved: \_\_\_\_\_ Not Approved: \_\_\_\_\_ Why not approved: \_\_\_\_\_

Contractor: \_\_\_\_\_ Contactor Address / Phone # \_\_\_\_\_

Bid Date: \_\_\_\_\_

Notes: \_\_\_\_\_